

Te Hui o Te Kaunihera ā-Rohe o Heretaunga Hastings District Council

#### **Civic Development Subcommittee Meeting**

### Kaupapataka

## **Agenda**

Te Rā Hui:

Meeting date:

Tuesday, 3 October 2023

Te Wā:

Time:

9.00am

**Council Chamber** 

**Ground Floor** 

*Te Wāhi:* Venue:

**Civic Administration Building** 

**Lyndon Road East** 

**Hastings** 

Te Hoapā:

**Democracy and Governance Services** 

Contact:

P: 06 871 5000 | E: democracy@hdc.govt.nz

Te Āpiha Matua:

Responsible

**Group Manager: Community Wellbeing & Services - Rebekah** 

Officer:

Dinwoodie

#### Civic Development Subcommittee

A Subcommittee of the Performance and Monitoring Committee.

#### Fields of Activity

The Civic Development Subcommittee is responsible for making delegated decisions and advising the Performance and Monitoring Committee by;

- Assisting Council in the allocation of Community Grants by;
  - Reviewing applications for Community Grants.
  - Setting appropriate performance measures to assist in the measurement of delivery of activities funded from Grants.
  - Allocation of grant funding within the budget allocation.
- Assisting Council in its general overview of procurement and tender activity by accepting tenders which exceed
  the Chief Executive's delegated authority to approve, for projects previously approved by Council or a Standing
  Committee within the delegated authority.
- Assisting Council by reviewing and considering submissions and deciding applications for temporary closure of roads.
- Recommending to Council the appointment of trustees to Te Mata Park Trust Board.
- Recommending to Council the appointment of directors to Hastings District Holdings Limited.
- Recommending to Council the appointment of List Members to the District Licencing Committee.
- Assisting Council by reviewing, considering nominations and recommending recipients of Civic Awards.
- Assisting Council by remaining cognisant of activities in the Community that deliver improved wellbeing and safety outcomes and advising Council how it can appropriately enable these activities.
- Providing guidance and oversight to Council Officers in the delivery of Council safety and security investments & initiatives to improve community wellbeing and sense of feeling safe and welcome.
- Providing guidance and oversight to Council Officers in the delivery of major Council civic development capital projects (projects as assigned to the Subcommittee).
- Providing comprehensive six monthly (and as required) Council civic development capital project progress reports to the Performance and Monitoring Committee.
- Providing guidance and oversight to Council Officers in the delivery of major Council and Council enabled Events.

Providing guidance and oversight to Council Officers in the active promotion of Hastings as a Visitor Destination.

#### Membership

- 8 Councillors.
- 1 Heretaunga Takoto Noa Māori Standing Committee Member appointed by Council.
- Group Manager: Planning and Regulatory Services to be a member only when the Subcommittee is recommending the appointment of List Members to the Hastings District Licensing Committee.
- The Chief Executive to be a member only when the Subcommittee is making a decision on tendering and procurement matters.
- The Group Manager Asset Management to be a member only when the Subcommittee is making a decision on tendering and procurement matters.
- The Transportation Manager to be a member only when the Subcommittee is making a decision on applications for temporary closure of roads.

- The Environmental Consents Manager to be a member only when the Subcommittee is making a decision on applications for temporary closure of roads.
- The Chair of the Te Mata Park Trust Board to be a member only when the Subcommittee is making a decision on appointments to the Te Mata Park Trust Board.
- The Chief Financial Officer to be a member only when the Subcommittee is making a decision on appointments to the boards of any Council Controlled Organisations.
- Chair appointed by Council.
- 2 Youth Council Members appointed by Council (non-voting)

#### Quorum

- a) A minimum of 3 members for Subcommittee meetings where the agenda items only address proposed temporary road closure applications (when there are no submitters).
- b) A minimum of 5 members for all other meetings of the Subcommittee.

#### **DELEGATED POWERS**

- 1) Authority to exercise all Council's powers, functions and authorities (except where prohibited by law or otherwise delegated) in relation to the allocation of grant funding within the budget allocation.
- 2) Authority to accept tenders for individual projects previously approved by the Council or a Standing Committee of the Council up to a value of \$10,000,000.
- 3) Responsibility to provide oversight and direction on tendering processes in general and/or specific issues relating to a particular project.
- 4) All the Council's powers and functions in respect to temporary prohibition of traffic under Section 342(1)(b) and clause 11(e) of Schedule 10 of the Local Government Act 1974.
- 5) Recommend to Council the appointment of Trustees to Te Mata Park Trust Board in accordance with the policy on Appointment of Trustees for Te Mata Park Trust Board, and the provisions of section 57 of the Local Government Act 2002.
- 6) Recommend to Council the appointment of director positions for Hastings District Holdings Limited in accordance with the Council's Policy on Appointment and Remuneration of Directors for Council Organisations.
- 7) Recommend to Council the recipients of Civic Awards.
- 8) Recommend to Council the appointment of List Members to the Hastings District Licensing Committee in accordance with the policy on the appointment of members for the District Licensing Committee, and the provisions of Sections 192 194 of the Sale and Supply of Alcohol Act 2012.



Tuesday, 3 October 2023

Te Hui o Te Kaunihera ā-Rohe o Heretaunga Hastings District Council

**Civic Development Subcommittee Meeting** 

## Kaupapataka

## **Agenda**

Mematanga: Koromatua

Membership: Chair: Councillor Malcolm Dixon

Ngā KaiKaunihera

Councillors: Michael Fowler, Damon Harvey, Henry Heke, Kellie Jessup,

Renata Nepe, Wendy Schollum and Kevin Watkins

Mayor Sandra Hazlehurst

Transportation Manager, Jag Pannu AND

Environmental Consents Manager, Caleb Sutton – for Item 4

Heretaunga Takoto Noa Māori Standing Committee appointee: Elizabeth

Waiwiri-Hunt

Two Youth Council appointees: Esta Chaplin and Nikki Mnyanyi

Tokamatua:

Quorum:

3 members - for meetings where the agenda items only address proposed temporary road closure applications (if no submitters).

5 members - for all other meetings of the Subcommittee.

Apiha Matua

Officer Responsible: Rebekah Dinwoodie – Group Manager: Community Wellbeing & Services

Te Rōpū Manapori me te

*Kāwanatanga* Democracy &

Governance Services:

Christine Hilton (Extn 5633)



### Te Rārangi Take

## **Order of Business**

#### **Apologies** – Ngā Whakapāhatanga

Apologies for Absence from Councillor Nepe and the two Youth Council appointees: Esta Chaplin and Nikki Mnyanyi have been received.

Leaves of Absence had previously been granted to Councillor Watkins and Mayor Hazlehurst

#### **2.0 Conflict of Interest** – He Ngākau Kōnatunatu

Members need to be vigilant to stand aside from decision-making when a conflict arises between their role as a Member of the Council and any private or other external interest they might have. This note is provided as a reminder to Members to scan the agenda and assess their own private interests and identify where they may have a pecuniary or other conflict of interest, or where there may be perceptions of conflict of interest.

If a Member feels they do have a conflict of interest, they should publicly declare that at the start of the relevant item of business and withdraw from participating in the meeting. If a Member thinks they may have a conflict of interest, they can seek advice from the General Counsel or the Manager: Democracy and Governance (preferably before the meeting).

It is noted that while Members can seek advice and discuss these matters, the final decision as to whether a conflict exists rests with the member.

#### Confirmation of Minutes – Te Whakamana i Ngā Miniti

Minutes of the Civic Development Subcommittee Meeting held Tuesday 5
September 2023.
(Previously circulated)

Temporary Road Closures - Hawke's Bay Car Club: Otene Road on Sunday, 15
October 2023; Cenotaph Remembrance Service: Russell Street on Saturday,
11 November 2023; and Taste of Hastings: Heretaunga Street on Friday, 10
November 2023

9

**5.0** Minor Items – Ngā Take Iti

#### **6.0** Urgent Items – Ngā Take Whakahihiri



Te Hui o Te Kaunihera ā-Rohe o Heretaunga

**Hastings District Council: Civic Development Subcommittee Meeting** 

## Te Rārangi Take

# Report to Civic Development Subcommittee

Nā:

From: Alf Johnson, Network Controls Manager

Temporary Road Closures - Hawke's Bay Car Club: Otene Road on

*Te Take:*Subject:

Sunday, 15 October 2023; Cenotaph Remembrance Service: Russell Street on Saturday, 11 November 2023; and Taste of

Hastings: Heretaunga Street on Friday, 10 November 2023

#### **1.0** Executive Summary – Te Kaupapa Me Te Whakarāpopototanga

1.1 The purpose of this report is to obtain a decision from the Civic Development Subcommittee regarding the following temporary road closures as requested below. This request arises from the need to inform and gain the approval of Hastings District Council ("the Council") in order to comply with the legal process to temporarily close the roads listed below:

**Hawke's Bay Car Club: Otene Road** from Elwood Road to Ruahapia Road. The road closures will be between **9.00am to 5.00pm on Sunday, 15 October 2023**. The purpose of these road closures is to hold a Car Sprint Event.

Cenotaph Remembrance Service: Russell Street from Eastbourne Street to Lyndon Road, Lyndon Road from Railway Road to Karamu Road South. The road closure will be between 7.00am to 1.00pm on Saturday, 11 November 2023. The purpose of this road closure is to hold a Remembrance Service.

**Taste of Hastings: Heretaunga Street** from Karamu Road to Warren Street between **2.00pm and 10.00pm on Friday, 10 November 2023**. **Warren Street** from Queen Street to Eastbourne Street between **4.30pm and 10.00pm on Friday, 10 November 2023**. The purpose of this road closure is to hold a Taste of Hastings event.

- 1.2 Given that there are no submissions in opposition to the closures and subject to the recommended conditions the activities can proceed and be undertaken in a safe and controlled environment. The risks associated with these closures can then be minimised and safely managed to Council's satisfaction.
- 1.3 As part of the notification process for these proposed temporary road closures, representatives visited each of the persons deemed to be affected by the proposed closures. This is an important

part of each proposed temporary road closure and is undertaken by the respective applicant involved. Details of the consultation undertaken in regard to the above proposed temporary road closures are set out under the consultation section of this report.

#### 2.0 Recommendations - Ngā Tūtohunga

- A) That the Civic Development Subcommittee receive the report titled Temporary Road Closures Hawke's Bay Car Club: Otene Road on Sunday, 15 October 2023; Cenotaph Remembrance Service: Russell Street on Saturday, 11 November 2023; and Taste of Hastings: Heretaunga Street on Friday, 10 November 2023.
- B) That the Civic Development Subcommittee <u>approve</u> the following temporary road closures subject to no submissions or objections having been received in respect of these applications:
  - i. Hawke's Bay Car Club: Otene Road from Elwood Road to Ruahapia Road. The road closure will be between 9.00am to 5.00pm on Sunday, 15 October 2023. The purpose of this road closures is to hold a Car Sprint Event.
  - ii. Cenotaph Remembrance Service: Russell Street from Eastbourne Street to Lyndon Road, Lyndon Road from Railway Road to Karamu Road. The road closures will be between 7.00am to 1.00pm on Saturday, 11 November 2023. The purpose of this road closure is to hold a Remembrance Service.
  - iii. Taste of Hastings: Heretaunga Street from Karamu Road to Warren Street between 2.00pm and 10.00pm on Friday, Friday, 10 November 2023. Warren Street from Queen Street to Eastbourne Street between 4.30pm and 10.00pm on 10 November 2023. The purpose of this road closure is to hold a Taste of Hastings event.

Subject to the following conditions to be complied with to the satisfaction of the Group Manager: Asset Management:

- i. These events are conducted in accordance with the New Zealand Transport Agency Code of Practice Temporary Traffic Management (CoPTTM).
- ii. The Traffic Management Plans including provision for appropriate signage is approved by the Traffic Management Coordinator acting under delegated authority.
- iii. The Traffic Management Plans must be complied with including any specific conditions.
- iv. Copies of the relevant liability insurance policies are received.
- v. That the cost of all advertising is met by the event organiser/s.
- vi. Emergency Services are contacted regarding the holding of this event with details of the dates, locations and time frames.
- vii. As per the Traffic Management Plan provisions all emergency services will be accommodated and access provided through the sites as required.
- viii. The applicant/s are responsible under the Health and Safety at Work Act 2015 for all health and safety risks associated with this activity and must take reasonably practicable steps to ensure the safety of all persons during these temporary road closures.
- ix. The applicant/s have in place at all times, appropriate Health and Safety measures (to prevent harm to any persons), including (but not limited to) any measures provided for in the submitted Health and Safety Plans including any conditions attached.

#### **3.0** Background – Te Horopaki

3.1 This report covers the application to hold events, being:

**Hawke's Bay Car Club: Otene Road** from Elwood Road to Ruahapia Road. The road closure will be between 9.00am to 5.00pm on Sunday, 15 October 2023.

**Cenotaph Remembrance Service: Russell Street** from Eastbourne Street to Lyndon Road, **Lyndon Road** from Railway Road to Karamu Road South. The road closure will be between 7.00am to 1.00pm on Saturday 11 November 2023.

**Taste of Hastings: Heretaunga Street** from Karamu Road to Warren Street between 2.00pm and 10.00pm and **Warren Street** from Queen Street to Eastbourne Street between 4.30pm and 10.00pm on Friday, 10 November 2023.

- 3.2 The above temporary road closures will be managed in accordance with the New Zealand Transport Agency Code of Practice Temporary Traffic Management (CoPTTM).
- 3.3 Traffic Management Plans (TMP) are to be submitted to the Hastings District Council and the TMPs will be approved for implementation, subject to the temporary road closure applications being approved.
- 3.4 A temporary road closure checklist, set out under the consultation section of the report, details the necessary items that the organiser/s need to submit as part of their application/s for the above proposed temporary road closures.
- 3.5 GIS maps showing the extent of the proposed temporary road closures are attached (Attachments 1, 2 and 3).
- 3.6 At the time of writing this report there were no planned road works that will affect or impact the above proposed temporary road closures.

#### **4.0 Discussion** – *Te Matapakitanga*

**Hawke's Bay Car Club – Otene Road** – This will be the second temporary closure of this section of Otene Road during the 2023 calendar year. (The average daily traffic count on this road is 856 vehicles).

#### **AND**

**Cenotaph Remembrance Service** – This will be the second temporary closure of this section of Russell Street during the 2023 calendar year. (The average daily traffic count on this road is 2500 vehicles).

#### AND

**Taste of Hastings** – This will be the third temporary closure of this section of Heretaunga Street during the 2023 calendar year. (The average daily traffic count on this road is 4724 vehicles).

The above roads have been chosen specifically for their suitability for holding the respective events or services.

#### **5.0 Options** – *Ngā Kōwhiringa*

Option One - Recommended Option - Te Kōwhiringa Tuatahi – Te Kōwhiringa Tūtohunga

5.1 Option A is the preferred option. It recommends the Subcommittee approve the temporary road closures detailed above, subject to conditions that will ensure public safety is maintained.

Temporary road closure options listed below:

- **Option A:** Approve some or all of the temporary road closures detailed above.
- Advantages: These events can proceed and contribute to the safe use of roads within the district for these proposed events.
- Disadvantages: Traffic will be impeded for a short period of time on specific roads.
- Option B: Do not approve any of the temporary road closures detailed above.
- Advantages: Traffic will not be impeded.
- Disadvantages: The proposed events may need to be cancelled.

#### **6.0** Next steps – Te Anga Whakamua

6.1 See above for options related to these proposed temporary road closures.

#### **Attachments:**

1 <u>↓</u>	Otene TMD	CG-17-14-00124
2₫	Remembrance Service TMD	CG-17-14-00125
3 <u>₽</u>	Taste Hastings event TMD	CG-17-14-00126

### Summary of Considerations - He Whakarāpopoto Whakaarohanga

#### **Fit with purpose of Local Government** - *E noho hāngai pū ai ki te Rangatōpū-ā-Rohe*

The Council is required to give effect to the purpose of local government as set out in section 10 of the Local Government Act 2002. That purpose is to enable democratic local decision-making and action by (and on behalf of) communities, and to promote the social, economic, environmental, and cultural wellbeing of communities in the present and for the future.

Link to the Council's Community Outcomes – Ngā Hononga ki Ngā Putanga ā-Hapori

This proposal promotes the cultural and social wellbeing of communities in the present and for the future.

#### Māori Impact Statement - Te Tauākī Kaupapa Māori

There are no known impacts for Tangata Whenua.

#### Sustainability - Te Toitūtanga

There are no known impacts for sustainability.

#### Financial considerations - Ngā Whakaarohanga Ahumoni

The advertising cost for these events are being met by the organiser/s of the events: Hawke's Bay Car Club and Hastings District Council.

#### **Significance and Engagement** - Te Hiranga me te Tūhonotanga

This decision/report has been assessed under the Council's Significance and Engagement Policy as being of low significance.

#### Consultation – internal and/or external - Whakawhiti Whakaaro-ā-roto / ā-waho

The organisers of the above events have been in contact with affected parties/residents. They advise that no issues have been raised to date regarding the above proposed temporary road closures.

Documents received in regard to each of the applications are set out at the end of this section.

- 1. Hawke's Bay Car Club Motor Sprint Event
- 2. Cenotaph Remembrance Service
- 3. Taste of Hastings

The above proposed temporary road closure/s have been posted on the Council website and formal public notification was published in the Hawke's Bay Today newspaper on Wednesday, 20 September 2023 and Monday, 21 September 2023.

The closing date for submissions was 4:00pm, Friday, 29 September 2023. No submissions were received.

If the road closure/s are approved, final formal public notification will be published for the Hawke's Bay Car Club – Motor Sprint Event and the Cenotaph Remembrance Service in the Hawke's Bay Today newspaper.

Items received:	Hawke's Bay Car Club.	Cenotaph Remembrance.	Taste of Hastings
Temporary Road Closure ap	plication Yes	Yes	Yes
Traffic Management Plan	Yes	Yes	Yes
Road Bond	Yes	NA	NA
Resident Visiting Form	Yes	Yes	Yes
Event Safety plan	Yes	NA	NA

#### **Risks**


Opportunity: To seek temporary road closures for the purpose of holding a cultural event and a sports event.

REWARD – Te Utu	RISK – Te TŪraru
Following an assessment of the risks involved in holding an event of this type organisers have applied for a temporary road closure to ensure the safety of the public.	Safety (public)


#### Rural Community Board – Te Poari Tuawhenua-ā-Hapori


There are no implications for the Rural Community Board. They have been advised of the proposed temporary road closures.















## Remembrance Service Nov 23

- Event 10:30pm to 1:00pm
- Road Closure 7:00am to 1:00pm
  - Russell St from Eastbourne St to Lyndon Rd
  - Lyndon St from Railway Rd to Karamu Rd St
- Disable and elderly parking inside as shown in TMD
- A parade of servicemen will start in Lyndon Rd approx.
   where shown and marched to the Cenotaph.
- Normal parking can be undertaken in Lyndon Rd of guest.










Permanent speed limit or RCA- designated operating speed (km/h)			≤50	60	70	80	90	100	
Traf	ffic signs		20						
A Sign visibility distance (m)			50	60	70	80	90	100	
В	B Warning distance (m)		50 or 30*	80	105	120	135	150	
С	Sign spacing (m)			25 or 15*	40	50	60	70	75
Safe	ety zones								
D	Longitudinal (m)+			10 or 5*	15	30	45	55	60
E	Lateral (m)+			1	1	1	1	1	1
	Lateral behind bar	rier install	ation	Α	s specifie	d by the In	stallation	Designer	
Тар									
G	Taper length (m)#	#		30	50	70	80	90	100
G	LV roads taper len	igth (m)#		25	30	35	40	45	50
K	Distance between	tapers (m	)	40	50	70	80	90	100
Deli	ineation devices								
Cone spacing in taper (m)			2.5	2.5	5	5	5	5	
Con	e spacing: Working	g space (m	)##	5	5	10	10	10	10
	arger minimum dist ninimum distances								
	n LV roads the long etain a single lane พ								
# 1.	On non-state high may be used whe accesses).								
				dth is less than 2.5m and the activity does not affect the live itted (with at least 5 cones at no greater than 2.5m centres).					
<ol><li>A taper of 30m (with cones at 2.5 (stop/go), portable traffic signals of the cones at 2.5 (stop/go).</li></ol>					entres) <mark>must be used where manual traffic control</mark> fiority give way are employed.				
## LV roads: double the cone spacing alo			ngside work	ing space	(eg 5 = 10	, 10 = 20)	_		
Lan	e widths (based on	permanei	nt spee	d or TSL if a	pplied)				
Speed (km/h) 30 40 50 60 70 80 90 100									


## Taste Hastings Nov 22

- Event 5:00pm to 9:30pm
- Heretaunga St (200 Block) Road closured from 2:00pm until 10:00pm
- Warren St Closed 4:30 (to allow traffic to leave)
- By Default Heretaunga St closed from Warren to Hastings St – one way
- Possible placing of "no parking cones" out from 2:00pm
   Warren St only to ensure no cars remaining on site
- NB all signs to be placed in position where visible and not likely to be moved – i.e. in a car park
- Note Karamu Rd Cones/cone bars and rope along trees
- NB Stage arriving just after 2pm Then tables and cheers


Taste Hastings event TMD Attachment 3




Taste Hastings event TMD Attachment 3



Taste Hastings event TMD Attachment 3





10. On roads with a permanent speed of

inspector remains on a footpath

is on an unsealed shoulder (or further away from the carriageway - including

75 of 76

less than 65km/h an amber flashing beacon is not required on the vehicle if the inspector or non-invasive works

Sign visibility distance (m)   50   60   70   80   90   100	Permanent speed limit or RCA- designated operating speed (km/h)			≤50		60	70	80	90	100	
B Warning distance (m) 50 or 30* 80 105 120 135 150 C Sign spacing (m) 25 or 15* 40 50 60 70 75  Safety zones  D Longitudinal (m)+ 10 or 5* 15 30 45 55 60 E Lateral (m)+ 1 1 1 1 1 1 1 1 1 1  Lateral behind barrier installation  As specified by the Installation Designer  Tapers  G Taper length (m)# 30 50 70 80 90 100 G LV roads taper length (m)# 25 30 35 40 45 50 K Distance between tapers (m) 40 50 70 80 90 100  Delineation devices  Cone spacing in taper (m) 2.5 2.5 5 5 5 5  Cone spacing: Working space (m)## 5 5 10 10 10 10  * Larger minimum distances apply on a minimum distances may be applied on other roads to accommodate road environment constraints.  * On LV roads the longitudinal and lateral safety zones may be reduced, or eliminated, in order to may be used when there are road environment constraints (eg intersections and commercial accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  By On TSL if applied)	Tra	ffic signs									
C Sign spacing (m) 25 or 15* 40 50 60 70 75  Safety zones  D Longitudinal (m)+ 10 or 5* 15 30 45 55 60  E Lateral (m)+ 1 1 1 1 1 1 1 1  Lateral behind barrier installation As specified by the Installation Designer  Tapers  G Taper length (m)# 30 50 70 80 90 100  G LV roads taper length (m)# 25 30 35 40 45 50  K Distance between tapers (m) 40 50 70 80 90 100  Delineation devices  Cone spacing in taper (m) 2.5 2.5 5 5 5 5  Cone spacing: Working space (m)## 5 5 10 10 10 10  * Larger minimum distances apply on a state highways and also on all multi-lane roads. The smaller minimum distances may be applied on other road to accommodate road environment constraints.  * On LV roads the longitudinal and lateral safety zones may be reduced, or eliminated, in order, to retain a single lane width. Positive traffic management and an appropriate TSL must be used.  # 1. On non-state highways with speeds 5 50km/h or less, a 10m taper (with cones at 1m centres) may be used when there are road environment constraints (eg intersections and commercial accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  ### LV roads: double the cone spacing alongside working space (eg 5 = 10, 10 = 20).	A Sign visibility distance (m)			50		60	70	80	90	100	
Safety zones  D Longitudinal (m)+ 10 or 5* 15 30 45 55 60  E Lateral (m)+ 1 1 1 1 1 1 1 1 1  Lateral behind barrier installation  Tapers  G Taper length (m)# 30 50 70 80 90 100  G LV roads taper length (m)# 25 30 35 40 45 50  K Distance between tapers (m) 40 50 70 80 90 100  Delineation devices  Cone spacing in taper (m) 2.5 2.5 5 5 5 5  Cone spacing: Working space (m)## 5 5 10 10 10 10  * Larger minimum distances apply on all state highways and also on all multi-lane roads. The smaller minimum distances may be applied on other road.  * On LV roads the longitudinal and lateral safety zones may be reduced, or eliminated, in order to retain a single lane width. Positive traffic management and an appropriate TSL must be used.  # 1. On non-state highways with speeds 50km/h or less, a 10m taper (with cones at 1m centres) may be used when there are road environment constraints (eg intersections and commercial accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5 in centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  ## LV roads: double the cone spacing alongside working space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent spee 1 or TSL if a oplied)	B Warning distance (m)		50 or 3	0*	80	105	120	135	150		
D Longitudinal (m)+ 10 or 5* 15 30 45 55 60  E Lateral (m)+ 1 1 1 1 1 1 1 1  Lateral behind barrier installation  Tapers  G Taper length (m)# 30 50 70 80 90 100  G LV roads taper length (m)# 25 30 35 40 45 50  K Distance between tapers (m) 40 50 70 80 90 100  Delineation devices  Cone spacing in taper (m) 2.5 2.5 5 5 5 5  Cone spacing: Working space (m)## 5 5 10 10 10 10  * Larger minimum distances apply on all state highways and also on all multi-lane roads. The smaller minimum distances may be applied on other roads to accommodate road environment constraints.  * On LV roads the longitudinal and lateral all safety zones may be reduced, or eliminated, in order to retain a single lane width. Positive transfer management and an appropriate TSL must be used.  # 1. On non-state highways with speeds 50km/h or less, a 10m taper (with cones at 1m centres) may be used when there are road environment constraints (eg intersections and commercial accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  **Larger minimum distances apply on all state highways and also on all multi-lane roads. The smaller minimum distances may be applied on other roads to accommodate road environment constraints.  **On LV roads the longitudinal and lateral safety zones may be reduced, or eliminated, in order to retain a single lane width. Positive transfer management and an appropriate TSL must be used.  #*LV roads: double the cone spacing along the working space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent spee) for TSL if a pplied)	С	Sign spacing (m)			25 or 15	5*	40	50	60	70	75
E Lateral (m)+ 1 1 1 1 1 1 1 1 1 1 Tapers  G Taper length (m)# 30 50 70 80 90 100  G LV roads taper length (m)# 25 30 35 40 45 50  K Distance between tapers (m) 40 50 70 80 90 100  Delineation devices  Cone spacing: Working space (m)## 5 5 10 10 10 10  * Larger minimum distances apply on all state highways and also on all multi-lane roads. The smaller minimum distances may be applied on other roads to accommodate road environment constraints.  * On LV roads the longitudinal and lateral asingle lane width. Positive traffic management and an appropriate TSL must be used.  # 1. On non-state highways with speeds 50km/h or less, a 10m taper (with cones at 1m centres) may be used when there are road environment constraints (eg intersections and commercial accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is pernitted (with at least 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  **LV roads: double the cone spacing alongside working space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent spee) of TSL if applied)	Safe	ety zones									
Lateral behind barrier installation  Tapers  G   Taper length (m)#   30   50   70   80   90   100    G   LV roads taper length (m)#   25   30   35   40   45   50    K   Distance between tapers (m)   40   50   70   80   90   100    Delineation devices  Cone spacing in taper (m)   2.5   2.5   5   5   5   5    Cone spacing: Working space (m)##   5   5   10   10   10   10    * Larger minimum distances apply on a minimum distances may be applied or other roads to accommodate road environment constraints.  * On LV roads the longitudinal and lateral safety zones may be reduced, or eliminated, in order to retain a single lane width. Positive traffic management and an appropriate TSL must be used.  # 1. On non-state highways with speeds 50km/h or less, a 10m taper (with cones at 1m centres) may be used when there are road environment constraints (eg intersections and commercial accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5 m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  ### LV roads: double the cone spacing alongside working space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent speed or TSL if a pplied)	D	Longitudinal (m)+			10 or 5	<b>5</b> *	15	30	45	55	60
Taper length (m)# 30 50 70 80 90 100  G LV roads taper length (m)# 25 30 35 40 45 50  K Distance between tapers (m) 40 50 70 80 90 100  Delineation devices  Cone spacing in taper (m) 2.5 2.5 5 5 5 5  Cone spacing: Working space (m)## 5 5 10 10 10 10  * Larger minimum distances apply on a minimum distances may be applied on other roads to accommodate road environment constraints.  * On LV roads the longitudinal and lateral safety zones may be reduced, or eliminated, in order to retain a single lane width. Positive traffic management and an appropriate TSL must be used.  # 1. On non-state highways with speeds SOkm/h or less, a 10m taper (with cones at 1m centres) may be used when there are road environment constraints (eg intersections and commercial accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5 m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  ### LV roads: double the cone spacing alongside work ing space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent spee 1 or TSL if applied)	Ε	Lateral (m)+			1		1	1	1	1	1
G Taper length (m)# 30 50 70 80 90 100 G LV roads taper length (m)# 25 30 35 40 45 50 K Distance between tapers (m) 40 50 70 80 90 100  Delineation devices  Cone spacing in taper (m) 2.5 2.5 5 5 5 5  Cone spacing: Working space (m)## 5 5 10 10 10 10  * Larger minimum distances apply on all state highways and also on all multi-lane roads. The smaller minimum distances may be applied on other roads to accommodate road environment constraints.  * On LV roads the longitudinal and lateral safety zone may be used when there are road environment accesses).  # 1. On non-state highways with speeds 50km/h or may be used when there are road environment accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with a tleast 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5 m centres) in centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  ### LV roads: double the cone spacing alongside working space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent spee)		Lateral behind bar	rier install	ation		Α	s specifie	d by the In	stallation	Designer	
G LV roads taper length (m)# 25 30 35 40 45 50  K Distance between tapers (m) 40 50 70 80 90 100  Delineation devices  Cone spacing in taper (m) 2.5 2.5 5 5 5 5  Cone spacing: Working space (m)## 5 5 10 10 10 10  * Larger minimum distances apply on a lastate highways and also on all multi-lane roads. The smaller minimum distances may be applied on other roads to accommodate road environment constraints.  * On LV roads the longitudinal and lateral safety zones may be reduced, or eliminated, jn order to retain a single lane width. Positive traffic management and an appropriate TSL must be used.  # 1. On non-state highways with speeds 50km/h or may be used when there are road environment accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permit and 2.5m and the activity does not affect the live late as 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5 in centres) in centres) in ust be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  ## LV roads: double the cone spacing alongside working space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent spee 1 or TSL if applied)	Тар	ers									
K Distance between tapers (m) 40 50 70 80 90 100  Delineation devices  Cone spacing in taper (m) 2.5 2.5 5 5 5 5  Cone spacing: Working space (m)## 5 5 10 10 10 10  * Larger minimum distances apply on all state highways and also on all multi-lane roads. The smaller minimum distances may be applied on other roads to accommodate road environment constraints.  * On LV roads the longitudinal and lateral safety zones may be reduced, or eliminated, in order to retain a single lane width. Positive traffic management and an appropriate TSL must be used.  # 1. On non-state highways with speeds may be used when there are road environment constraints (eg intersections and commercial accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  ## LV roads: double the cone spacing alongside working space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent spee 1 or TSL if a pplied)	G	Taper length (m)#	<i>‡</i>		30		50	70	80	90	100
Delineation devices  Cone spacing in taper (m)  2.5  2.5  5  5  5  5  6  Cone spacing: Working space (m)##  5  5  10  10  10  10  * Larger minimum distances apply on all state highways and also on all multi-lane roads. The smaller minimum distances may be applied on other roads to accommodate road environment constraints.  * On LV roads the longitudinal and lateral safety zones may be reduced, or eliminated, in order to retain a single lane width. Positive traffic management and an appropriate TSL must be used.  # 1. On non-state highways with speeds solom/h or may be used when there are road environment accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  ## LV roads: double the cone spacing alongside work ing space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent speed)	G	LV roads taper len	igth (m)#		25		30	35	40	45	50
Cone spacing in taper (m)  2.5  2.5  5  5  5  5  6  Cone spacing: Working space (m)##  5  5  10  10  10  10  10  *  ** Larger minimum distances apply on all state highways and also on all multi-lane roads. The smaller minimum distances may be applied on other roads to accommodate road environment constraints.  * On LV roads the longitudinal and lateral safety zones may be reduced, or eliminated, in order to retain a single lane width. Positive traffic management and an appropriate TSL must be used.  # 1. On non-state highways with speeds 50km/h or less, a 10m taper (with cones at 1m centres) may be used when there are road environment constraints (eg intersections and commercial accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  ## LV roads: double the cone spacing alongside work ing space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent speed or TSL if a pplied)	K	Distance between	tapers (m	1)	40		50	70	80	90	100
** Larger minimum distances apply on all state highways and also on all multi-lane roads. The smaller minimum distances may be applied on other roads to accommodate road environment constraints.  ** On LV roads the longitudinal and lateral safety zones may be reduced, or eliminated, in order to retain a single lane width. Positive traffic management and an appropriate TSL must be used.  #* 1. On non-state highways with speeds 50km/h or less, a 10m taper (with cones at 1m centres) may be used when there are road environment accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  ##* LV roads: double the cone spacing alongside working space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent speeds)	Deli	ineation devices									
<ul> <li>* Larger minimum distances apply on all state highways and also on all multi-lane roads. The smaller minimum distances may be applied on other roads to accommodate road environment constraints.</li> <li>* On LV roads the longitudinal and lateral safety zones may be reduced, or eliminated, in order to retain a single lane width. Positive traffic management and an appropriate TSL must be used.</li> <li># 1. On non-state highways with speeds 50km/h or less, a 10m taper (with cones at 1m centres) may be used when there are road environment constraints (eg intersections and commercial accesses).</li> <li>2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).</li> <li>3. A taper of 30m (with cones at 2.5m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.</li> <li>## LV roads: double the cone spacing alongside working space (eg 5 = 10, 10 = 20).</li> <li>Lane widths (based on permanent speed or TSL if applied)</li> </ul>	Cone spacing in taper (m)			2.5		2.5	5	5	5	5	
<ul> <li>minimum distances may be applied on other roads to accommodate road environment constraints.</li> <li>On LV roads the longitudinal and lateral safety zones may be reduced, or eliminated, in order to retain a single lane width. Positive traffic management and an appropriate TSL must be used.</li> <li># 1. On non-state highways with speeds 50km/h or less, a 10m taper (with cones at 1m centres) may be used when there are road environment accesses).</li> <li>2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).</li> <li>3. A taper of 30m (with cones at 2.5m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.</li> <li>## LV roads: double the cone spacing alongside working space (eg 5 = 10, 10 = 20).</li> <li>Lane widths (based on permanent speed or TSL if a pplied)</li> </ul>	Con	e spacing: Working	g space (m	)##	5		5	10	10	10	10
retain a single lane width. Positive traific management and an appropriate TSL must be used.  1. On non-state highways with speeds 50km/h or less, a 10m taper (with cones at 1m centres) may be used when there are road environment constraints (eg intersections and commercial accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  ## LV roads: double the cone spacing alongside working space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent speed or TSL if applied)											
may be used when there are road environment constraints (eg intersections and commercial accesses).  2. On all roads where the shoulder width is less than 2.5m and the activity does not affect the live lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  ## LV roads: double the cone spacing alongside working space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent speed or TSL if applied)											
lane, a 10m shoulder taper is permitted (with at least 5 cones at no greater than 2.5m centres).  3. A taper of 30m (with cones at 2.5m centres) must be used where manual traffic control (stop/go), portable traffic signals or priority give way are employed.  ## LV roads: double the cone spacing alongside working space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent speed or TSL if applied)	# 1.	may be used whe									
(stop/go), portable traffic signals or priority give way are employed.  ## LV roads: double the cone spacing alongside working space (eg 5 = 10, 10 = 20).  Lane widths (based on permanent speed or TSL if applied)											
Lane widths (based on permanent speed or TSL if applied)	3						affic contr	ol			
Lane widths (based on permanent speed or TSL if applied)	## L	## LV roads: double the cone spacing alo				vork	ing space	(eg 5 = 10	), 10 = 20)		
				-	1			70	80	90	100